

10-30-00

A

Patent Application
Docket No. 34651-00404USPT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Uwe König and Hans-Christian Schaub

Entitled: METHOD FOR PARALLEL SEARCHING A LOOK-UP TABLE

To the Assistant Commissioner
for Patents
Box Patent Application
Washington, D.C. 20231

CERTIFICATE OF MAILING BY EXPRESS MAIL

"EXPRESS MAIL" Mailing Label No. EL524960540US
Date of Deposit: October 27, 2000
I hereby certify that this paper or fee is being
deposited with the U.S. Postal Service "Express
Mail Post Office to Addressee" service under
37 CFR 1.10 on the date indicated above and is
addressed to the Assistant Commissioner for
Patents, Washington, D.C. 20231

Type or Print Name Carol Mitchell
Carol Mitchell
Signature

Dear Sir:

REQUEST FOR FILING A NATIONAL PATENT APPLICATION

Transmitted herewith for filing, please find the following:

- ☒ 1. Specification, claims and abstract of the above-referenced patent application having
 27 pages.
- ☒ 2. Two (2) sheet(s) of drawing(s) (___ formal / ☒ informal) comprising Figures 1-4.
- ☒ 3. Combined Declaration and Power of Attorneys (___ signed ☒ unsigned).
- ___ 3A. No filing fee, Oath, or Declaration is enclosed pursuant to 37 C.F.R 1.53(d).
- ___ 4. Information Disclosure Statement along with Form PTO-1449 and references.
- ___ 5. This is a: ___ Continuation-In-Part; ___ Divisional; ___ Continuation;
 ___ substitute Application (MPEP 201.09) of Application Serial No. ___ filed ___;
 ___ reissue of U.S. Patent No. ___ filed on ___.

An extension to extend the life of the above prior Application to at least the date of filing hereof

(One box must be marked)

- (a) ☐ is concurrently being filed in that prior Application,
(b) ☐ was previously filed in that prior Application,
(c) ☐ is not necessary for copendency.

☐ 6. Attached is an assignment to Telefonaktiebolaget L M Ericsson (publ). Please return the recorded assignment to the undersigned.

☐ 7. Priority is claimed under 35 U.S.C. § 119(e) based on filings in the U.S.

	<u>Application No.</u>	<u>Filing Date</u>
(1)	<input type="checkbox"/>	<input type="checkbox"/>
(2)	<input type="checkbox"/>	<input type="checkbox"/>
(3)	<input type="checkbox"/>	<input type="checkbox"/>

☐ (No.) Certified copy (copies) ☐ are attached; or ☐ were previously filed on ☐.

☐ 8. Attached: ☐ (No.) verified statement(s) establishing "small entity" status under 37 CFR § 1.9 and 1.27.

☒ 9. Attached:

☒ Return Postcard
☐ (Other)

☐ 10. Preliminary Amendment:

Prior to a first Office Action, kindly amend the Application as follows:

- X 11. The following Filing Fee calculation is based on the claims filed less any claims canceled by the Preliminary Amendment of Item 10.


					SMALL ENTITY RATE		LARGE ENTITY RATE		
BASIC FEE					\$355	<u>OR</u>	\$710	=	\$ 710.00
	NUMBER FILED			NUMBER EXTRA					
TOTAL CLAIMS	<u> 18 </u>	-20	=	<u> 0 </u> (at least 0)	x 9	<u>OR</u>	x 18	=	+\$
INDEP. CLAIMS	<u> 3 </u>	- 3	=	<u> 0 </u> (at least 0)	x 40	<u>OR</u>	x 80	=	+\$
If any <u>proper</u> multiple dependent claim (ignore improper) is present (Enter \$0.00 if this is a <u>reissue</u> application.)					+\$130	<u>OR</u>	+\$260	=	+\$
If assignment is x'd (item 6), add recording fee \$40.00									\$
Attached is a Rule 47 Petition (inventor refuses to sign or cannot be reached) \$130									+\$ <u> </u>
TOTAL FILING FEE									= \$ 710.00

- X 12. A check in the amount of \$710.00 to cover the Filing Fee calculated in Item 11 is attached. Please charge any deficiency or credit any overpayment to Deposit Account No. 10-0447.
13. Please charge my Deposit Account No. 10-0447 in the amount of \$ to cover the Filing Fee calculated in Item 11. This sheet is attached in duplicate.
- X 14. The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and may be required under 37 CFR 1.16-1.18 (missing or insufficiencies only) now or hereafter relative to this application and for the resulting Official Document under 37 CFR 1.20, and to have and cause any necessary petition for extension of time to be filed and any fees necessary to be paid for said extension of time OR credit any overpayment to our Deposit Account No. 10-0447, for which purpose a


duplicate copy of this sheet is attached. **The Commissioner is not authorized to charge the issue fee until/unless an issue fee transmittal form is filed.**

Respectfully submitted,

JENKENS & GILCHRIST, P.C.

By: 
Name: Hsin-Wei Luang
Reg. No. 44,213

Jenkins & Gilchrist, P.C.
1445 Ross Avenue
Suite 3200
Dallas, Texas 75202
(214) 855-4736
(214) 855-4300 (fax)



METHOD FOR PARALLEL SEARCHING A LOOK-UP TABLE

BACKGROUND OF THE INVENTION

Technical Field of the Invention

The present invention relates in general to methods for looking up values stored in a table and, in particular, to a method for searching values stored in a table by breaking the

5 table into subtables.

Description of Related Art

The present invention is a method for looking up values in a table. However, because it is difficult to discuss the method of the present invention without a framework, the following description of related art focuses on ATM networks and VPI/VCI look-up

tables. It should be noted that the present invention may be applied to looking up other values in an ATM or other networks such as, for example, IP or peer-to-peer networks.

An ATM network is composed of nodes, interfaces, links, and virtual resources, just like other network schemes. There are two types of ATM nodes: network nodes and customer premise nodes. Network nodes are located inside an ATM network, while customer premise nodes are located at the peripheries of an ATM network. Network nodes connect to each other or to customer premise nodes. Customer premise nodes connect to network nodes, to user interfaces, or to other types of networks.

Nodes perform the switching and/or data transport functions within an ATM network. A data interface, or “switch,” is located within each network or customer premise node. On network nodes, this interface is called the network node interface (NNI), and on customer premise nodes this interface is called the user network interface (UNI). UNIs are responsible for transferring data, while NNIs are responsible for both transferring data and providing signaling procedures to operate and control the ATM network.

The NNI and UNI are connected to each other by physical links such as coaxial cables. The physical links are then electronically subdivided into virtual paths and virtual channels. Each physical link can carry multiple virtual paths, and each virtual path can carry

multiple virtual channels. In fact, up to 256 virtual paths can be defined for each physical link, and up to 65,536 virtual channels can be defined within each virtual path.

Each virtual path and each virtual channel can be identified by a specific number. For the virtual path, this number is called the virtual path identifier (VPI); for the virtual
5 channel, this number is called the virtual channel identifier (VCI). When combined, the VPI/VCI numeric identifier points to one and only one virtual channel in one and only one virtual path connected to a particular node. Though unique for a particular node, the VPI/VCI identifier may be used a second (or third, or fourth, etc.) time for other non-interconnected nodes within the same ATM network.

10 The virtual channels in virtual paths on physical links are used to carry segments of user data called cells. Each cell contains a header section and a payload section. The entire cell can carry 53 bytes of information, with the header section carrying 5 bytes of information and the payload section carrying 48 bytes of information. Large blocks of user data are broken down to fit into the data-carrying area of the cell, but the payload section
15 is 48 bytes long, even if the information carried within the payload section takes less than 48 bytes of space.

The header section carries all the instructions a cell needs to travel from its origination location to its destination location. The instructions include, for example, data flow and data transfer information. The instructions also identify which virtual path and which virtual channel the cell must use when traveling from one node to another—i.e., the header stores VPI/VCI information.

An ATM cell travels between nodes of an ATM network using a technique called label swapping. Because of timing, traffic, or congestion, when a cell changes physical links at nodes, the cell may also have to change virtual channels and/or virtual paths. If there is a change in the virtual channel and/or virtual path, the cell's VPI and/or VCI must also be changed so that the cell's VPI and VCI identify the correct virtual path and/or virtual channel carrying the cell.

To change the VPI/VCI stored in a cell, three sets of VPI/VCI must be used: the actual incoming VPI/VCI stored in the cell, a tabulated incoming VPI/VCI stored in the node's memory, and an outgoing VPI/VCI stored in the node's memory and associated with the tabulated incoming VPI/VCI. When a switch is first initialized, a table is generated containing all the possible incoming VPI/VCI and all the possible outgoing VPI/VCI. Further, each tabulated incoming VPI/VCI is matched with an outgoing VPI/VCI. This

table is stored in the node's memory. When a cell containing an actual incoming VPI/VCI arrives at the node, the actual incoming VPI/VCI is matched with a tabulated incoming VPI/VCI and a set of actions are performed related to the actual incoming VPI/VCI. The actions include, but are not limited to, swapping the actual incoming VPI/VCI with the outgoing VPI/VCI associated with the tabulated incoming VPI/VCI.

There are three general methods of looking up the actual incoming VPI/VCI, matching, and then performing a set of actions related to the actual incoming VPI/VCI. The first method uses the incoming VPI/VCI itself to address the table. Here, the VPI/VCI is entered into a function that maps the 28 bit value to a smaller value, with the value being smaller than 28. The table then has 2^n entries. Alternatively, the 28 bit value can be split into two or more values which are then used to address different tables.

The second prior art way of looking up the actual incoming VPI/VCI, matching, and then performing an action related to the incoming VPI/VCI (such as replacing it with an outgoing VPI/VCI) is to simply search the entire VPI/VCI table. Here, the actual incoming VPI/VCI is compared with various tabulated incoming VPI/VCI values in the table. When the incoming VPI/VCI matches a tabulated incoming VPI/VCI in the table, an algorithm is used to perform an action including, but not limited to, swapping the incoming VPI/VCI

with an outgoing VPI/VCI, erasing the incoming VPI/VCI, or counting the incoming or outgoing VPI/VCI.

5 A significant problem with the above-described methods is that they work well when web traffic is slow. However, the methods limit the number of cells passing through a switch if traffic increases. This is so because a switch has only a limited time—the time it takes for the switch to process the cell—to look up an outgoing VCI/VPI and perform the action needed to be performed. As the number of cells passing through the switch increases, the number of tabulated and outgoing VPI/VCI also increases, thereby making the table larger and larger. The increased number of cells also increases the number of look-
10 ups per time period for both the existing table look-up methods described above. The larger table and the greater number of look-ups all decrease the available time for matching the incoming VPI/VCI with the outgoing VPI/VCI. Thus, the time it takes to look up a corresponding VPI/VCI can bottleneck at the node.

15 A third way for searching a numeric table solves the bottleneck problem but, at the same time, creates problems for other computing power related issues. The third way for searching table entries compares all the values in the table with the search term simultaneously. Since all the values in the table must be compared at the same time, this

7

SUMMARY OF THE INVENTION

A technical advantage of the present method is that the method reduces the time needed to look up values in a table or the amount of simultaneous look-ups.

Another technical advantage of the present method is that the method can increase
5 the number of cells passing through a switch for a given time period and/or speeds up data transfer.

Another technical advantage of the present method is that the method allows for faster searching of a table without having to increase the hardware/processing power.

The present invention is a method for parallel searching for data stored in a table.
10 The present invention searches the entire table by first breaking the larger table into a plurality of smaller subtables. The time period needed by the switch to process a cell determines the number of subtables needed. Thus, the number of subtables can change as the traffic flow per switch changes.

Once the original table has been subdivided into subtables, all the subtables are
15 searched simultaneously.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and apparatus of the present invention may be had by reference to the following detailed description when taken in conjunction with the accompanying drawings herein:

5 FIGURE 1 is a graphical representation of an ATM data cell;

FIGURE 2 is a portion of an ATM network;

FIGURE 3 is a pictorial representation of the prior art method of searching a VPI/VCI routing table; and

10 FIGURE 4 is a pictorial representation of the present invention using parallel subtable searching techniques.

DETAILED DESCRIPTION OF THE DRAWINGS

The following is a detailed description of the present invention, a method to look up values in a table by first breaking the table into subtables. Though the present invention may be applied to any operation where looking up values in a table is required, for illustrative purposes, the description below focuses on looking up VPIs and VCIs in an ATM network. It should be understood that the present invention may be used to look up other values in ATM or any other type of network including, but not limited to, IP or peer-to-peer networks.

FIGURE 1 is a pictorial representation of an ATM cell 10, used to transfer data in an ATM network. Cell 10 can be further subdivided into a header subsection 11 and a payload subsection 12. Cell 10 can store 53 bytes of information, with header 11 storing five bytes and payload 12 storing 48 bytes.

Header 11 contains locations for storing seven different pieces of information. The generic flow control (GFC) location 13 is found at the beginning of header 11. The GFC location can store four bits of information. The GFC is optional, and if not used, the 4 bits may be used by the VPI. The VPI location 14 is found next to the GFC location 13 and can

store eight bits of information; the VCI 15 location is found next to the VPI location 14, and can store sixteen bits of information. The payload type (PT) location 16 can store two bits of information and is found next to the VCI location 15. One bit of reserved space 17 is found next to the PT location 16. The cell loss priority (CLP) location 18 also stores one
5 bit of information and is found next to the reserved space 17 location. The header error check (HEC) location 19 is found next to the CLP location 18. HEC 19 can store eight bits of information and is the final element in header 11.

Payload 12 is found behind header 11. The data 20 transmitted by cell 10 is stored in the 48 bytes in payload 12.

10 FIGURE 2 shows a plurality of nodes within a partial ATM network 30. It should be understood that the configuration and connections between the nodes in FIGURE 2 are used here as an example only. The nodes within actual ATM networks may be simpler or more complex than that shown in FIGURE 2.

Partial ATM network 30 is composed of nodes 31, 32, 33, and 34. A virtual path
15 35 connects node 31 to node 32. A virtual path 36 connects node 32 to node 33. A virtual path 37 connects node 32 to node 34. While FIGURE 2 depicts only one virtual path

connecting the various nodes to each other, it should be understood that a plurality of virtual paths may exist between any two nodes of an ATM network.

5 A plurality of virtual channels can exist within each virtual path. However, for illustrative purposes, FIGURE 2 only shows a limited number of virtual channels within each virtual path. In FIGURE 2, virtual channels 38 and 39 are located within virtual path 35, virtual channel 40 is located within virtual path 36, and virtual channel 41 is located within virtual path 37.

10 A switch is located at each ATM node. FIGURE 2 shows switch 42 located at node 31, switch 43 located at node 32, switch 44 located at node 33, and switch 45 located at node 34. Switches 42, 43, 44, and 45 ensure cell 10 is transmitted from its origination node (not shown) to its destination node (not shown) by being properly routed from one virtual path and/or virtual channel to another virtual path and/or virtual channel between the nodes.

15 When a connection for transmitting data is established between an origination node (not shown) and a destination node (not shown), each node in the pathway the data is to travel is identified, along with each virtual channel and each virtual path. Since the data may travel on different virtual paths and different virtual channels between nodes, each node contains a table 46 (FIGURE 3) in its memory that matches the VPI and VCI of the

incoming cell 10 with an outgoing VPI and VCI and/or other related data. The table 46 is set up when the switch is first initialized.

It should be noted that table 46 may have separate sections within the larger table for VPI and VCI or may be one table storing a combined VPI/VCI pair. For illustrative purposes only, the following description of both the prior art method and the present invention assumes the numbers are stored in the table as a combined VPI/VCI pair. It should be understood, however, that the present invention may also be used when the VPI and the VCI are looked up separately.

When cell 10 travels from node 31 to node 33, cell 10 is first assigned a VPI and a VCI. As an example, cell 10 has a VPI of number "35" and a VCI of number "38," each corresponding with the virtual path and virtual channel cell 10 is to travel. The VPI identifier "35" is stored in VPI memory location 14, and the VCI identifier "38" is stored in VCI memory location 15. Cell 10 is then sent from node 31 to node 32 on virtual path 35 and virtual channel 38. Node 32 recognizes the VPI identifier "35" and the VCI identifier "38" as an incoming VPI/VCI pair.

In order for cell 10 to pass from node 32 to node 33, there must be a change in virtual path as well as a change in virtual channel. FIGURE 2 shows the virtual path

changes from 35 to 36, and the virtual channel changes from 38 to 40. Node 32 reads the incoming VPI/ VCI, matches the incoming VPI/VCI with an outgoing VPI/VCI within node 32's memory, and swaps the incoming VPI/VCI in VPI memory location 14 and VCI memory location 15 with the matching VPI/VCI.

5 FIGURE 3 shows a prior art method of reading an actual incoming VPI/VCI, matching the actual incoming VPI/VCI with a tabulated incoming VPI/VCI stored in node 32's memory, locating the outgoing VPI/VCI associated with the tabulated incoming VPI/VCI, and performing a number of functions related to the outgoing VPI/VCI, including, but not limited to, replacing the actual incoming VPI/VCI in VPI memory
10 location 14 and VCI memory location 15 with the outgoing VPI/VCI. It should be understood that the prior art method described below is used as an example only and thus the exact method for reading, comparing, and swapping the VPI/VCI information is unimportant so long as the tabulated incoming VPI/VCI and their associated outgoing VPI/VCI are stored in one table.

15 FIGURE 3 shows table 46 which contains tabulated incoming VPI/VCI along with their associated outgoing VPI/VCI. Table 46 may be stored as a matrix having *i* number of cell compartments. To initiate the comparing and swapping steps, counter 50 first

generates a number j , where $j \leq i$. The number j is then used as a pointer which points to a cell compartment in table 46, where a tabulated incoming VPI/VCI is stored along with its associated outgoing VPI/VCI. The tabulated incoming VPI/VCI at location j is then compared with the actual incoming VPI/VCI at comparator 51. If the tabulated incoming VPI/VCI does not match the actual incoming VPI/VCI, then j is changed to another number, for example $j + 1$, and a tabulated incoming VPI/VCI at location $j + 1$ is compared with the actual incoming VPI/VCI. This step is repeated until the actual incoming VPI/VCI matches a tabulated incoming VPI/VCI. When the tabulated incoming VPI/VCI matches the actual incoming VPI/VCI, then the outgoing VPI/VCI information associated with the tabulated incoming VPI/VCI is passed to match decoder/selector 52. At match decoder/selector 52, the outgoing VPI/VCI information in cell j is swapped with (or another predetermined action is performed) the actual incoming VPI/VCI information so that VPI location 14 and VCI location 15 of cell 10 now stores the outgoing VPI/VCI. Cell 10 is then sent to node 33 on the virtual path and virtual channel identified by the outgoing VPI and VCI.

FIGURE 4 is a pictorial representation of an embodiment of the present invention. Generally, the present invention is a method of breaking down a large table 60 containing

09/20/2017 09:28:50

tabulated information into a plurality of subtables 61 having the same information and then searching through the plurality of subtables 61 to locate a specific piece of tabulated information. A detailed method for accomplishing the above method is disclosed below. It should be understood that the detailed method is disclosed as an example only and that various alternate methods can be used for reading a first piece of data, comparing this first piece of data with a second piece of data, and—if the first piece of data matches the second piece of data—performing a desired action, including, but not limited to, swapping, modifying, or removing the VPI/VCI information and/or swapping, modifying, or removing data sets associated with the VPI/VCI. For ease of description, the following detailed description will discuss swapping the VPI/VCI only. It should be readily apparent to those skilled in the art that the present method can easily be modified to perform other actions such as modifying or removing VPI/VCI information or data sets associated with the information.

As shown in FIGURE 4, table 60 is a matrix having n number of cell compartments, with each cell compartment storing a tabulated incoming VPI/VCI and its associated outgoing VPI/VCI. Counter 62 generates a number P , where $P \leq n$. P is used as a pointer pointing to each cell compartment in table 60. As P points from the first cell compartment

in table 60 to the n th cell compartment in table 60, tabulated incoming VPI/VCI and its associated outgoing VPI/VCI are copied to subtables number 1 through K . Each subtable is a matrix containing m number of cells for storing tabulated incoming VPI/VCIs and their associated outgoing VPI/VCIs. The number of subtables, K , is found using the following equation:

$$K = \frac{n}{t}$$

where t is the time it takes for a node, for example node 32, to process cell 10. The number m is determined using the following equation:

$$x = \frac{n}{K}, \text{ where if the remainder of } \frac{n}{K} \text{ is 0, then } m = x;$$

$$\text{if the remainder of } \frac{n}{K} \text{ is not 0, then } m \text{ is the next larger integer to } x$$

Note if $\frac{n}{K}$ is a power of 2, for example 2^p , and Q bits are necessary to address K subtables, then all subtables can be addressed as one table with $P+Q$ address bits.

K does not have to be recalculated for every cell 10 that passes through node 32. As can be seen above, *K* is inversely related to *t* so that *K* increases when *t* decreases. Thus, the number of subtables should only be recalculated and a new set of subtables 61 built when the amount of data transfer per time unit increases above a preset criteria for a particular node.

Once subtables 61 have been built, a second pointer, *r*, is generated where $r \leq m$. Pointer *r* is used to simultaneously point to one cell compartment within each subtable 1 through *K*. The tabulated incoming VPI/VCIs stored within each cell compartment of subtables 1 through *K* are simultaneously compared with the actual incoming VPI/VCi at comparator 63. The algorithm used to compare the tabulated incoming VPI/VCIs with the actual incoming VPI/VCi can be any algorithm known in the art of numeric comparison algorithms. If none of the tabulated incoming VPI/VCIs stored in cell compartments *r* of subtables 1 through *K* matches the actual incoming VPI/VCi, then *r* is changed to, for example *r*+1, and the comparison process is repeated. If, however, the tabulated incoming VPI/VCi in one of the cell compartments *r* of subtables 1 through *K* matches the actual incoming VPI/VCi, then the outgoing VPI/VCi associated with the matched tabulated incoming VPI/VCi is passed to match decoder/selector 64. At this point, counter 62 can,

but needs not be, stopped. Match decoder/selector 64 replaces the actual incoming VPI/VCI stored in VPI location 14 and VCI location 15 with the outgoing VPI/VCI and/or takes other specific actions related to the incoming VPI/VCI, such as modifying or removing the incoming VPI/VCI. The algorithm used to swap the actual incoming

5 VPI/VCI with the outgoing VPI/VCI may be any algorithm known in the art of number swapping algorithms.

After swapping the actual incoming VPI and VCI with the outgoing VPI/VCI, cell 10 is passed to node 33 on the virtual path and the virtual channel specified by the outgoing VPI and VCI.

10 There may be cases in which it is acceptable that the probability for finding a matching entry is below 100%. If so, then only a portion of each subtable – for example, 80% of each table – will be searched. If the actual incoming VPI/VCI cannot be matched with a tabulated incoming VPI/VCI located within, for example, the 80% of the subtables, various other methods for processing the cell known in the art can be used. For example,

15 the actual VPI/VCI may be stored in computer memory and searched later in the 20% of each subtable not yet searched, when the amount of data transfer per frame unit decreases.

There may also be cases where cell processing time t changes but the number of subtables need not be recalculated. Sometimes, the cell processing time varies only by a small increment such as, for example, 2-3 time units. Rather than recalculating the subtables, the cell processing time t can be delayed (or additional delay removed) rather than
5 having to recalculate the subtables. Note the method for splitting the table in subtables remains the same except t is selected so that either the subtables need not be recalculated or the splitting of the main table into subtables can be optimized.

Although a preferred embodiment of the method and apparatus of the present invention has been illustrated in the accompanying Drawings and described in the foregoing
10 Detailed Description, it will be understood that the invention is not limited to the embodiment disclosed, but is capable of numerous rearrangements, modifications and substitutions without departing from the spirit of the invention as set forth and defined by the following claims.

We claim:

- 1 1. A method for searching a first table, comprising the steps of:
2 storing a first value in a computer memory location;
3 constructing a plurality of subtables by dividing said first table into said plurality of
4 subtables;
5 searching said plurality of subtables simultaneously to match said first value with a
6 second value, said second value located in one of said plurality of subtables; and
7 performing an operation on said first value based on the identity of said second
8 value.
- 9 2. The method of Claim 1, wherein said operation replaces said first value in said
10 computer memory location with a third value associated with said second value.
- 11 3. The method of Claim 1, wherein said operation modifies said first value in said
12 computer memory location.

1 4. The method of Claim 1, wherein said operation modifies a data set associated with
2 said first value in said computer memory location.

3 5. The method of Claim 1, wherein said operation removes said first value from said
4 computer memory location.

5 6. The method of Claim 1, wherein said first value is selected from a group comprising
6 a VPI, a VCI, or a VPI/VCI pair.

7 7. The method of Claim 1, wherein said second value is selected from a group
8 comprising a VPI, a VCI, or a VPI/VCI pair.

9 8. The method Of Claim 1, wherein said third value is selected from a group
10 comprising a VPI, a VCI, or a VPI/VCI pair.

9. A method for conveying a data packet from a first node to a second node comprising the steps of:

reading a first VPI and a first VCI from said data packet at said first node;

storing said first VPI and said first VCI in a computer memory location;

simultaneously searching for a second VPI and a second VCI in parallel in a plurality of subtables, one subtable in said plurality of subtables containing said second VPI, and said second VCI matching said first VPI and said first VCI;

replacing said first VPI and said first VCI in said data packet with a third VPI and a third VCI, said third VPI and said third VCI associated with said second VPI and said second VCI; and

conveying said data packet to said second node.

10. The method of Claim 9, further comprising the steps of:

storing said first VPI and said first VCI as a first VPI/VCI pair, storing said second VPI and said second VCI as a second VPI/VCI pair, and storing said third VPI and said third VCI as a third VPI/VCI.

1 11. The method of Claim 9, wherein said plurality of subtables are constructed by
2 dividing a first table, said first table containing said second VPI and said second VCI and
3 said third VPI and said third VCI associated with said second VPI and said second VCI.

4 12. The method of Claim 11, wherein said first VPI and said first VCI are stored as a
5 first VPI/VCI pair, said second VPI and said second VCI are stored as a second VPI/VCI
6 pair, and said third VPI and said third VCI are stored as a third VPI/VCI pair.

7 13. The method of Claim 11, wherein the number of said plurality of subtables is
8 determined by dividing a number of entries in said first table by a value representing the time
9 it takes for said data packet to pass through said first node.

- 1 14. An ATM network, comprising:
- 2 a plurality of customer premise nodes,
- 3 a plurality of network nodes;
- 4 a plurality of physical links connecting said customer premise nodes to said network
- 5 nodes; and
- 6 at least one data packet transmitted through a plurality of physical links between said
- 7 plurality of customer premise nodes and said plurality of network nodes, said data packet
- 8 including a first VPI and a first VCI, said first VPI and said first VCI replaced by a second
- 9 VPI and a second VCI when said data packet travels through a first network node in said
- 10 plurality of network nodes, said second VPI and said second VCI determined by searching
- 11 a plurality of subtables in parallel, with one subtable in said plurality of subtables containing
- 12 a third VPI and a third VCI associated with said second VPI and said second VCI, said third
- 13 VPI and said third VCI matching said first VPI and said first VCI.

1 15. The ATM network of Claim 14, wherein said first VPI and said first VCI are stored
2 as a first VPI/VCI pair, said second VPI and said second VCI are stored as a second
3 VPI/VCI pair, and said third VPI and said third VCI are stored as a third VPI/VCI pair.

4 16. The ATM network of Claim 14, wherein said plurality of subtables are constructed
5 by dividing up a first table containing a third VPI and a third VCI associated with said
6 second VPI and said second VCI, said third VPI and said third VCI matching said first VPI
7 and said first VCI.

8 17. The ATM network of Claim 16, wherein said first VPI and said first VCI are stored
9 as a first VPI/VCI pair, said second VPI and said second VCI are stored as a second
10 VPI/VCI pair, and said third VPI and said third VCI are stored as a third VPI/VCI pair.

11 18. The ATM network of Claim 16, wherein the number of said plurality of subtables
12 is obtained by the number of entries in said first table divided by a value representing the
13 time it takes said data packet to travel through said first network node in said plurality of
14 network nodes.

METHOD FOR PARALLEL SEARCHING IN VPI/VCI LOOK-UP TABLE

ABSTRACT OF THE DISCLOSURE

5 A method and system are disclosed for parallel searching a table by first breaking the larger table into a plurality of smaller subtables. Once the larger table has been subdivided into subtables, all the subtables are searched simultaneously (in parallel). When a match is detected, a predetermined operation is performed.




FIGURE 1




FIGURE 2

002201 82285960

09698728.103700 00/20T 82/286560




FIGURE 3




FIGURE 4

RULES 63 AND 67 (37 C.F.R. 1.63 and 1.67)
DECLARATION AND POWER OF ATTORNEY

FOR UTILITY/DESIGN/CIP/PCT NATIONAL APPLICATIONS

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; and

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **METHOD FOR PARALLEL SEARCHING A LOOK-UP TABLE**, the specification of which: (mark only one)

- X (a) is attached hereto.
 (b) was filed on _____ as Application Serial No. _____ and was amended on _____ (if applicable)
 (c) was filed as PCT International Application No. PCT/_____ on _____ and was amended on _____ (if applicable).
 (d) was filed on _____ as Application Serial No. _____ and was issued a Notice of Allowance on _____.
 (e) was filed on _____ and bearing attorney docket number _____.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above or as allowed as indicated above.

I acknowledge the duty to disclose all information known to me to be material to the patentability of this application as defined in 37 CFR § 1.56. If this is a continuation-in-part (CIP) application, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the Office all information known to me to be material to patentability of the application as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this CIP application.

I hereby claim foreign priority benefits under 35 U.S.C. § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application on which my priority is claimed or, (2) if no priority is claimed, before the filing date of this application:

PRIOR FOREIGN PATENTS

<u>Number</u>	<u>Country</u>	<u>Month/Day/Year Filed</u>	<u>Date first</u>	<u>Date</u>	<u>Priority Claimed</u>	
			<u>laid-open or Published</u>	<u>patented or Granted</u>	<u>Yes</u>	<u>No</u>
_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____

I hereby claim the benefit under 35 U.S.C. § 120/365 of any United States application(s) listed below and PCT international applications listed above or below:

PRIOR U.S. OR PCT APPLICATIONS

Application No. (series code/serial no.) Month/Day/Year Filed Status(pending, abandoned, patented)

I hereby appoint:

TIMOTHY G. ACKERMANN, Reg. No. 44,493
THOMAS E. ANDERSON, Reg. No. 37,063
BENJAMIN J. BAI, Reg. No. 43,481
MICHAEL J. BLANKSTEIN, Reg. No. 37,097
MARY JO BOLDINGH, Reg. No. 34,713
MARGARET A. BOULWARE, Reg. No. 28,708
ARTHUR J. BRADY, Reg. No. 42,356
MATTHEW O. BRADY, Reg. No. 44,554
DANIEL J. BURNHAM, Reg. No. 39,618
THOMAS L. CANTRELL, Reg. No. 20,849
RONALD B. COOLLEY, Reg. No. 27,187
THOMAS L. CRISMAN, Reg. No. 24,846
STUART D. DWORK, Reg. No. 31,103
WILLIAM F. ESSER, Reg. No. 38,053
ROGER J. FRENCH, Reg. No. 27,786
JANET M. GARETTO, Reg. No. 42,568
JOHN C. GATZ, Reg. No. 41,774
RUSSELL J. GENET, Reg. No. 42,571
J. KEVIN GRAY, Reg. No. 37,141

STEVEN R. GREENFIELD, Reg. No. 38,166
J. PAT HEPTIG, Reg. No. 40,643
SHARON A. ISRAEL, Reg. No. 41,867
JOHN R. KIRK JR., Reg. No. 24,477
PAUL R. KITCH, Reg. No. 38,206
TIMOTHY M. KOWALSKI, Reg. No. 44,192
HSIN-WEI LUANG, Reg. No. 44,213
JAMES F. LEA III, Reg. No. 41,143
ROBERT W. MASON, Reg. No. 42,848
ROGER L. MAXWELL, Reg. No. 31,855
ROBERT A. McFALL, Reg. No. 28,968
LISA H. MEYERHOFF, Reg. No. 36,869
STANLEY R. MOORE, Reg. No. 26,958
RICHARD J. MOURA, Reg. No. 34,883
MARK V. MULLER, Reg. No. 37,509
P. WESTON MUSSELMAN JR. Reg. No. 31,644
DANIEL G. NGUYEN, Reg. No. 42,933
SPENCER C. PATTERSON, Reg. No. 43,849

RUSSELL N. RIPPAMONTI, Reg. No. 39,521
STEPHEN G. RUDISILL, Reg. No. 20,087
HOLLY L. RUDNICK, Reg. No. 43,065
J.L. JENNIE SALAZAR, Reg. No. 45,065
KEITH W. SAUNDERS, Reg. No. 41,462
JERRY R. SELINGER, Reg. No. 26,582
GARY B. SOLOMON, Reg. No. 44,347
ROBERT C. STRAWBRICH, Reg. No. 36,692
STEVE Z. SZCZEPANSKI, Reg. No. 27,957
ANDRE M. SZUWALSKI, Reg. No. 35,701
ALAN R. THIELE, Reg. No. 30,694
TAMSEN VALOIR, Reg. No. 41,417
TAMSEN VALOIR, Reg. No. 41,417
RAYMOND VAN DYKE, Reg. No. 34,746
BRIAN D. WALKER, Reg. No. 37,751
GERALD T. WELCH, Reg. No. 30,332
HAROLD N. WELLS, Reg. No. 26,044
WILLIAM D. WIESE, Reg. No. 45,217

all of the firm of **JENKENS & GILCHRIST, P.C.**, 3200 Fountain Place, 1445 Ross Avenue, Dallas, Texas 75202-2799, as my attorneys and/or agents, with full power of substitution and revocation, to prosecute this application, provisionals thereof, continuations, continuations-in-part, divisionals, appeals, reissues, substitutions, and extensions thereof and to transact all business in the United States Patent and Trademark Office connected therewith, to appoint any individuals under an associate power of attorney and to file and prosecute any international patent application filed thereon before any international authorities, and I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/organization who/which first sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct them in writing to the contrary.

Please address all correspondence and direct all telephone calls to:

Hsin-Wei Luang
Jenkins & Gilchrist, P.C.
3200 Fountain Place
1445 Ross Avenue
Dallas, Texas 75202-2799
214/855-4736
214/855-4300 (fax)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAMED INVENTOR(S)

1	Uwe König		
	Full Name	Inventor's Signature	Date
	Von-Voigts-Rhetz-Str. 10 D-31135 Hildesheim Germany		German
	Residence (city, state, country)		Citizenship
	Von-Voigts-Rhetz-Str. 10 D-31135 Hildesheim Germany		
	Post Office Address (include zip code)		

(FOR ADDITIONAL INVENTORS, check here X and add additional sheet for inventor information regarding signature, name, date, citizenship, residence and address)

004207" 8243550

2	Hans-Christian Schaub		
	Full Name	Inventor's Signature	Date
	Glider Str. 8 D-38116 Braunschweig Germany		German
	Residence (city, state, country)		Citizenship
	Glider Str. 8 D-38116 Braunschweig Germany		
	Post Office Address (include zip code)		